

Zebra® GK420™ Desktop Printer

Best Value in a Basic Desktop Printer

G-Series™ GK420: Always a Perfect Fit

Zebra's compact G-Series desktop thermal printers are the best in their class. And the G-Series GK420 model—built with Zebra durability and reliability—provides the best value in the “basic” desktop thermal category. It's the perfect fit wherever you need a low-priced, space-saving printer for 4-inch-wide labels, tags or receipts.

An Easy Fit

The easy-to-use design provides simple, fast media loading and, when you choose the GK420t™ direct thermal/thermal transfer version, the easiest ribbon-loading on the market. And with the smallest footprint in a 4-inch desktop printer, the GK420d™ direct thermal model sleekly slips into your most congested workspaces.

Fast Performer

The GK420 features fast 5-inches-per-second print speed to meet your low- to medium-volume printing applications. And with its 32-bit processor, it increases your productivity with fast “first label out” and no between-label delay.

Simple to Integrate and Manage

- With both Zebra programming languages on board, GK420 printers fit into legacy EPL™ desktop printer environments as well as with Zebra tabletop and mobile printers that use the powerful ZPL® language.
- The GK420 comes with dual connectivity (USB, serial) for easy integration into existing systems. For increased network throughput, choose the 10/100 Ethernet option.
- IT managers will appreciate the remote printer management and host status reporting features that make their jobs easier and reduces printer downtime.

Well-suited to any industry and a variety of applications, reliable GK420 printers are a smart investment, and always a perfect fit.



Quick Specs*

STANDARD FEATURES

EPL and ZPL co-resident on all models
5"/127 mm (outside diameter) media capacity
Quick and easy ribbon loading
Smallest footprint in class
Head-up sensor

PRINTER SPECIFICATIONS

Print Speed

5"/127 mm per second (maximum)

Print Width

4.09"/104 mm

Print Length

39"/991 mm

Print Method

Direct thermal or thermal transfer

Resolution

203 dpi/8 dots per mm

Memory

8 MB SDRAM; 4 MB Flash

Connectivity

Serial and USB standard
10/100 Ethernet (optional)

www.zebra.com/g-series

*Specifications subject to change without notice.

©2008 ZIH Corp. EPL and all product names and numbers are Zebra trademarks, and Zebra, the Zebra head graphic and ZPL are registered trademarks of ZIH Corp. All rights reserved. All other trademarks are the property of their respective owners.



identWERK GmbH
Talweg 2
D-74906 Bad Rappenau

Fon: ++49 (0) 72 64 / 95 91-0
Fax: ++49 (0) 72 64 / 95 91-20
www.identWERK.de

identWERK
auto ID solutions